


CENTER 318

DATA LOGGER HYGRO THERMOMETER

CE



Features:

- *Interchangeable Digital Probes.*
- *Thermistor Sensor For Temperature Measurement, Fast Response Time*
- *Dew Point Measurement.*
- *Extending Cable Available.*

CENTER®



Data Logger HYGRO THERMOMETER

FEATURE

- Interchangeable Digital Probes.
- Thermistor Sensor For Temperature Measurement, Fast Response Time
- Dual Display.
- Dew Point Measurement.
- PC Interface.
- 16,000 Records Data Logger.
- Auto Shut Off For Battery Saving.
- Extending Cable Available.
- Tilt Stand.



SPECIFICATIONS

Sensor:

Electronic capacitance polymer film sensor/NTC

Measurement Range:

Temperature: -20°C~60°C, -4°F~140°F

Humidity: 0%RH~100%RH

Resolution: 0.1°C/0.1°F/0.1%RH

Accuracy:

Temperature: $\pm 0.8^{\circ}\text{C}$, $\pm 1.5^{\circ}\text{F}$

Humidity: $\pm 2.0\% \text{RH}$

Response Time: (@t90; in slowly moving air)

Humidity: 60 sec.

Temperature: 10sec.

Display: LCD, 2 lines.

Parameters Displayed:

Relative humidity, temperature and dew point.

Battery Type: 9V battery

Battery Lifetime: Approx. 80 hours

Dimensions:

Meter: 185(L)×65(W)×36(H)mm

Probe: 94(L)×15mm Dia

Weight: Approx. 285g

Accessories:

9V Battery, Instruction Manual, Windows software,
USB Cable, RS-232 Cable(Optional), Carry Case,
AC Adapter(Optional).



33%RH / 75%RH
Humidity Cell (OPTIONAL)



LED Back Light

* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER®

CENTER TECHNOLOGY CORP.

4/F., NO.415, Jung-Jeng Rd., 238 Shu-Lin, Taipei, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http: //www.centertek.com



Distributed by:

Authorized Distributor
APL ASIA CO., LTD.
11/129-132 Moo.5 Lamlukka Rd., T.Kookut, A.Lamlukka, Pathumthani 12130
Thailand. TEL. 0-2995-4461-3, FAX. 0-2995-4464
www.apl-asia.com
EMAIL: sales@apl-asia.com
LINE@: @APL-ASIA