



PRODUCT SPECIFICATION

LPT-M-SO2 Transmitter

Digital (Modbus®) Transmitter with Electrochemical Sulphur Dioxide (SO₂) Sensor

Dimensions: Size	5.0" X 5.0" X 2.8" (127 mm x 127 mm x 71 mm) (dimensions without optional splash guard)
Weight	5.0" X 5.0" X 3.3" (127 mm x 127 mm x 84 mm) (dimensions with optional splash guard) 14 ounces (400 g)
Construction	ABS / Polycarbonate blend, water/dust tight, corrosion resistant (meets IP54 standard with optional splash guard installed)
Sensor: Type	Electrochemical
Life Span	Approximately 2 years (application dependent)
Gases Detected	Sulphur Dioxide (SO ₂)
Sensor Range	0 – 20 ppm standard
System Power	3-wire: VDC: 12-30 VDC, 3-Watts 4-wire: VAC: 12-27VAC, 3-VA
Temperature	-30°C to +50°C (-22°F to 122°F), -40°C (-40°F) with LCD heater option
Humidity	15 to 90% non-condensing
Indicators	LCD digital display, back lit, 128 X 64 pixel graphic (optional heater - applications to -40C)
Signal	Modbus® RS-485 RTU
Relay	One dry contact relay rated 2-amps @ 30v S.P.D.T.
Audible	Internal audible alarm (user controlled)
Minimum Detection	0.1 ppm (with regular calibration maintenance of sensor)
Accuracy	+/- 0.1 ppm @ STP, across measurement range at time of calibration with SO ₂ and at calibration concentration + calibration gas concentration error
Repeatability	5% (with regular calibration maintenance of sensor)
Sensitivity Drift	Zero: <+/-0.8 ppm (with regular calibration maintenance of sensor) +20 to -20C Zero: <+/- 3 ppm (with regular calibration maintenance of sensor) +20C to +50C Span: <4% signal per month (with regular calibration of sensor)
Response Time	<35 seconds (0-10 ppm) T ₉₀
Resolution	Display resolution 0.01 ppm, sensor resolution: 0.02 ppm
Warm Up Time	5- minutes after power up (to full operation)
Cross Sensitivity	H ₂ S 20 ppm = <3, NO ₁₀ ppm = <130, Cl ₂ 10 ppm = <-60, NO 50 ppm = <+/-2, CO 400 ppm = <1.6, H ₂ 400 ppm = <0.3, C ₂ H ₄ 400 ppm = <40, NH ₃ 20 ppm = <0.1
Safety	Automatic resetting thermal overload fuse (reset capabilities to 500 times)
Wiring	4-wire VAC/VDC, 16 awg, 4-conductor shielded network wiring (daisy chain)
Sensor Mounting	Heavier than air, 6" from the floor
Monitoring Area	3000 sq. ft.
Certifications	CSA: C22.2 NO.205-12 UL: UL508 (Edition 17): 2007 CE: EMC Directive 2004/108/EC, EN50270:2006, Type-1 & EN61010 FCC
Note	Never install gas detectors in the direct path of moving air.

Rev. 1803-1