

ECONOMINITM





Authorized Distributor APL ASIA CO.,LTD.

PERFORMANCE

(a) 21 dba

MAX FLOW	MAX HEAD	MAX LIFT	
8 L/ HOUR	8 METRES	5 METRES	

Self-priming and running silent when either wet or dry, the ECONOMINI™ condensate removal pump provides installers complete flexibility when it comes to positioning the pump. With a compact, lightweight package the ECONOMINI™ can retrofit around existing pipe work or cornering trunking as well as into the ceiling void.

SENSING OPTION

ECONOMINI™ pump available with:

CR PLUG	TEMPERATURE SENSOR
X87-514	X87-515



All of the BLUEDIAMOND® pumps have the ability to run dry without burning out. Enabling them to remove any liquids, preventing organic growth inside the tubing.




QUIET

Quiet in all stages of operation and not only when set to quiet mode or relying on a soft start setting.


UNIT 3.5-8 KW


PERFORMANCE



DIMENSIONS (MM)

V (VERTICAL)





H (HORIZONTAL)

DISCHARGE PIPE RUN



8 M	3 M
7 M	6 M
6 M	9 M
5 M	12 M
4 M	15 M
3 M	18 M
2 M	21 M
1 M	24 M

ECONOMINI™ can be mounted in orientation up to 5m away from the A.C.