

CENTER 388 Infrared Refrigerant Leakage Detector



CENTER 388 Refrigerant Leakage Detector is the perfect tool for maintaining the air-condition or a cooling system with compressor and Refrigerant. This unit uses a newly developed infrared gas sensor which is extremely sensitive to variety of general used Refrigerant.



DC 5V Jack(388)

SPECIFICATIONS

- Microprocessor Control with advanced digital signal processing.
- Multi color visual display.
- High-median-Low leak sensitivity selector.
- Infrared gas sensor.
- Detection of R-134a, R-404A, R-410A, R-407C, R22, R32, HFO-1234yf... Freon gas.
- Sensitivity As Small: 3g / year
- 15.5" (40 CM) flexible stainless probe.
- Ambient concentration reset.
- Peak function – find leaks in noisy environments.
- Mute function.
- Auto-matic zero and background compensation.
- Warm-up Time: 45 Seconds.
- Operating Temperature: 0 to 40°C (32 to 104°F)
- Dimension / Weight: 254 x 71 x 54 mm / 416g(with batteries)
- Power Usage: 3.7vdc rechargeable lithium Batteries.
- Battery Life: Approx. 8hrs; Low battery indication.
- AC Adapter: @5V 1A

R-134a
R-404A
R-410A
R-407C
R-22
R-32
HFO-1234yf
 ... more Refrigerants Gas



CENTER 383 Combustible Gas Detector



CENTER 383 is designed as a high performance combustible gas detector with extremely sensitivity to variety of general used combustible gases. The unit is built in newly developed heated semiconductor gas sensor and microprocessor control to provide reliable digital signal processing. Adjustable leak sensitivity level and 7 LED visual indicators also offer the users the ease and convenience of operations.



SPECIFICATIONS

- Heated Semiconductor Gas Sensor.
- High-Low Leak Sensitivity Selector.
- 7 LED Tri-colored Visual Leak Level Indicator.
- Variable Intensity Audible Alarm.
- Ambient Concentration Reset.
- 15.5" (40CM) Flexible Stainless Probe.
- Detection of METHANE/HYDROCARBON....Combustible Gases.
- Sensitivity As Small 5 ppm.
- Warm-up Time: 90 Seconds.
- Operating Temperature: 0 to 40°C (32 to 104°F)
- Dimension / Weight: 21.7 x 6.6 x 5.6 cm / 400g(with batteries)
- Power Source: 4 AA Size Alkaline Batteries.
- Battery Life: Approx. 40hrs
- Low Battery Indication.
- Reference Leak Source Included.

STANDARD ACCESSORIES

Model	Battery	Operation Manual	Carrying Case	Leak Check Bottle	AC Adapter
CENTER388	Li-ion Battery	●	●	●	●
CENTER383	Size AA Batery	●	●	●	●



METHANE/HYDROCARBON

Gasoline, propane, natural gas or fuel oil
 ... more Combustible Gases

Authorized Distributor

APL ASIA CO., LTD.
 11/129-132 Moo.5 Lamlukka Rd., T.Kookut, A.Lamlukka,
 Pathumthani 12130 Thailand.
 TEL. 0-2995-4461-3, FAX. 0-2995-4464
 www.apl-asia.com
 EMAIL : sales@apl-asia.com
 LINE@ : @APL-ASIA

