

INDOOR AIR QUALITY(IAQ) MONITOR



Best helper to increase your rating while applying **LEED** green building certificate



Table 2. Points for Continuous Indoor Air Monitoring					
Parameter	Data requirement	Minimum limit	IAQ	Enhanced IAQ	Points*
Carbon dioxide (CO ₂)	95 th percentile value	1000 ppm		800 ppm	3 (minimum IAQ limit), 4 (enhanced IAQ limit)
PM2.5	Daily average	15 µg/m ³		12 µg/m ³	3 (minimum IAQ limit), 4 (enhanced IAQ limit)

By improving the CO₂ and PM2.5 concentration indoor and providing continuous monitoring record, at most 8 points is added to your LEED rating.

Health index level	AQI category	Breakpoints (µg/m ³ , 24H average)
1	Good	0.0~12.0
2	Moderate	12.1~35.4
3	Unhealthy for sensitive groups	35.5~55.4
4	Unhealthy	55.5~150.4
5	Very Unhealthy	150.5~250.4
6	Hazardous	250.5~350.4
7	Hazardous	350.5~500

Ordering Code

VZ7710AZ, 7710 PM2.5/CO₂ Logger
VB17729A, 5V USB adaptor with 4 plugs

*Available for EB project

PM2.5, CO₂, HUMIDITY, TEMP. MONITOR/DATALOGGER 7710

- Large LED displays PM2.5, Health index, CO₂, humidity and temperature.
- 12000 times auto logging. USB2.0 plug and play. No need to operate through specific software.
- Wall mount display with 3-color light bar to provide PM2.5/CO₂ hazardous level indicator from far distance
- High accuracy laser optical PM2.5 sensor
- NDIR (non-dispersive infrared) waveguide CO₂ tech
- CO₂ automatic background calibration(called ABC) for long time drift compensation



Model	7710
<u>Measuring range</u>	
PM2.5	0~999 ug/m ³
CO ₂	0~9999 ppm,
Temperature	-10.0~60.0°C (14~140°F)
Humidity	0.1~99.9% RH
Resolution	1ug/m ³ , 1ppm, 0.1°C/F, 0.1%RH
<u>Accuracy</u>	
PM2.5	0-100: +/-10 ug/m ³ ; 101~999: +/-10% rdg.
CO ₂	+40ppm +/-3% of reading (400~2000ppm), Other range is 10% of reading
Temperature	+0.6°C/+0.9°F
Humidity	+5%RH (at 25°C, 10~90%RH); +7%RH (at 25°C, other range)
Warm-up time	10 seconds
<u>Response time</u>	
PM2.5	<30 seconds (90% step change)
CO ₂	<30 seconds (63% step change)
Tair	<2 mins (90% step change)
Humidity	<20 minutes (90% step change)
Auto Logging	12000 times records
Operating condition	0~50°C, 0~95% RH (avoid condensation)
Storage condition	-20~50°C, 0~95% RH (avoid condensation)
Power supply	5VDC USB type C port
Power consumption	<500mA
Meter size (LxWxH,mm)	257 x 168 x 45.5 mm (L x W x T)
IP rating	IP20
Weight	610g
Standard package	Meter, manual, Type C cable, Hanging & filtering accessories.
Optional accessory	100~240V to 5V@0.6A adaptor with 4 plugs (US.EU.UK. AU)

Areas of application: Widely used in the office building, school, exhibition hall, shopping mall, meeting room, fitness center, restaurant and other public places where **energy bill**, personal **comfort** and **healthy** are important.

