


# HEAT STROKE PREVENTION LOGGER



## Professional WBGT Logger 87786

- Check Indoor/Outdoor WBGT, TA/TG& Humidity
- Plug & Play. Software and USB driver are not required
- Generate csv report without using extra PC software.
- Completely user re-programmable. 8 languages, sampling rate, start delay time and ID setting.
- Designed with capacitance humidity sensor with dust filter to get accurate reading and extend sensor life time
- Audible beeper and backlight for danger zone warning



Model	87786
Temp. range	0~50°C
Temp. resolution	0.1°C/°F
Temp. accuracy	+/-0.6°C
Humidity. range	0.1%~99.9%RH
Humidity resolution	0.1%RH
Humidity accuracy	+/-3%RH (at 25°C, 10~90%RH, others +/-5%RH)
Globe Temp. (inside black ball)	0~80°C
Globe Temp. Acc.	Indoor: +/-1 °C (at 15~40°C), others 1.5 °C outdoor: +/-1.5 °C (at 15~40°C), others 2 °C
WBGT temp. range	0~50°C
WBGT Alarm Range	20~50°C
Sampling rate	1, 5, 10, 30, 60, 90, 120 mins
Start delay time	0, 5, 30, 45, 60, 90, 120 mins
Memory points	12000 readings, each contains WBGT, TA, TG and RH
Black ball size (mm)	Dia. 75, height:75
Stabilization time	15 ~25 minutes typical
RH% Self calibration	YES
Battery life	>200hour
LCD size (mm)	50(H)x32(W)
Operation temp.	0~50°C
Operation RH%	Humidity < 80%
Storage temp.	-20~50°C
Storage RH%	Humidity < 90%
Dimension (mm)	302(H)x75(W)x36.7(T)
Weight	~300g
Battery	AAA x4pcs

Standard Package Meter/Battery/Manual/mini USB cable/paper box

### Optional



**CAL. SALT BOTTLE**  
P/N: VZ87781ST2  
(33% & 75%)  
For 87782/87785/87786  
Calibration.

### WBGT indicator

Green backlight  
(26.7~29.4°C)



Yellow backlight  
(29.4~31°C)



Red backlight  
(31~32.2°C)



Red flashing  
backlight  
(Above 32.2°C)



### Ordering Code

VZ87786AZ, 87786 meter  
VZ87781ST2, salt bottles

