




IP67 Waterproof Thermometer with Long Probe 8891

- The most cost effective waterproof temperature monitor with super large LCD and long probe
- 0.1 degree resolution and high accuracy
- IP67 waterproof meter and external probe
- Wall mounted design for long time using
- 4 alkaline AAA batteries provides 1 year battery life
- Stainless long & durable external probe
 - length:0.5m
 - diameter:5mm
 - handle length(nylon+glass fiber)
 - cable length(silicon):1.5m



Model	8891
Temp. Range (thermistor)	-10~110°C(-14~230°F)
Temp. Resolution	0.1°C(0.1°F)
Temp. Accuracy	+/-1°C(+/-1.6°F)
Temp. Response time	2 minutes typical
LCD update time	10 seconds
LCD size (mm, HxW)	45x96
Operating temp.	0~50°C
Operating RH%	Humidity < 80%
Storage temp.	-20~50°C
Storage RH%	Humidity < 90%
Meter Dimension(mm,LxWxT)	122x85x30
Meter Weight	~200g
Probe size(mm)	
Length	500
Diameter	5
Handle length(mm)	65
Cable length(mm)	1500
Probe Weight	~80g
Battery	AAA ALKALINEx 4pcs
Standard Package	Meter, probe, probe holder, battery, manual, plain box
Optional Accessory	External probe

Safe, Quick and Easy to read the boiler temperature in faraway place!!




EXTERNAL PROBE
 P/N: VZ889PNL
 Length: 500mm
 Diameter: 5mm
 Handle length: 65mm
 Cable length: 1500mm

IP	6	5	Description
Ingress Protection	Solids (Dust etc.)	Liquids (Water etc.)	IP65: protected against jets of water
			IP66: protected against strong jets of water
			IP67: protected against immersion in water up to 1 meter for 30 minutes
			IP68: protected against immersion in water under pressure for long periods

Ordering Code

VZ8891AZ, 8891 long probe thermometer
 VZ889PNL, 8891 long probe
 VM4889PD, stainless probe holder



STAINLESS PROBE HOLDER
 P/N: VM4889PD
 Included in standard package to offer you steady probe support!



*Available for EB project