

Necool

IRD-300 Infrared Leak Detector

(4 Level sensitivity+Alarm probe led + 3 UV light+ 2 led light)

10 years sensor lifetime

2g or 3g/year sensitivity per EN14624

Quick charging lithium ion battery

2.8-inch color LCD display

Superior sensitivity and strong anti-interference performance

Detect all HCFCs, HFCs, HFOs, (including A2Ls)

State-of-the-art infrared sensor

Sensitivity multilevel adjustment, 2g/a(stationary); 3g/a (in motion)

Flashing light tip, loud beeper and LCD bar graph

Two high- intensity LED inspection light, unafraid of dark environments (only IRD-300)

Three LED UV lights with 395-415 nm wave length is optimum for a/c dye fluorescence only (IRD-300)

Two rechargeable 18650 lithium batteries can be disassembled and replaced

Audio mute mode

Item No.	IRD-300
Refrigerants	CFCs/HCFCs/HFCs/HFOs
Sensor life	10 years
Sensitivity	2g/yr
Alarm mode	Audible and visual alarm and flashing probe LED
Response time	Instantaneous
Warm-up me	30s
Auto off me	10 minutes of inactivity
Battery	2*18650 Lithium battery
Operating temperature	-10°C~50°C
Overall size	210*60*36 inch.
Probing length	420 mm.
Four sensitivity levels	Low, Medium, High, Super high



รับประกันตัวเครื่อง 1 ปี



บริษัท เอพีแอล เอเชีย จำกัด

WWW.APL-ASIA.COM

Tel 02-9954461-3 Email: sales@apl-asia.com Line: @APL-ASIA
11/129-132 หมู่ 5 ถนน ลำลูกกา 5 ตำบลคูคต อำเภอลำลูกกา ปทุมธานี 12130

SCAN HERE

