

COMBO WATER METER



IP67 Handheld pH/EC/TDS/SALT/D.O. 86031

- Big LCD with multiple parameters simultaneously:
PH, Conductivity or TDS or Salinity, Dissolved oxygen & Temperature
- Fast D.O. Measuring
- Accurate replaceable probes with anti-collision cap
- Auto ranging for conductivity measurement
- Manually altitude/salinity compensation for D.O. Reading
- Multiple points calibration: 3 points for pH, 1 point for D.O., 4 points for conductivity



Auto Power Off



Auto Temp. Compensation



Memory Recall



Manual Logging



Metric/Imperial



Low Battery



IP67



PH

EC/TDS/SALT

D.O.

Probes



Accessory

Model	86031
pH range/resolution	2.00~12.00/resolution :0.01
pH accuracy	+/-0.1
Cond. range	0~199.9, 0~1999uS/cm, 0~19.99, 0~150.0mS/cm
Cond. accuracy	+/-1% F.S +/- 1 digit
Cond. resolution	0.1uS/cm, 1uS/cm, 0.01mS/cm, 0.1mS/cm
TDS. Range (f is TDS factor)	0~199.9*f, 0~1999*f ppm, 0~19.99*f, 0~150.0*f ppt
TDS. Accuracy/res.	+/-1% F.S +/- 1 digit; res.:0.1,1ppm;0.01, 0.1ppt
TDS Factor	0.30~1.00
Salinity range	0~10.00ppt; 0~42.0ppt (SEA WATER)
Salinity accuracy/res.	+/-1% F.S +/- 1 digit; res.: 0.01 ppt, 0.1ppt
D.O. range	0.0~199.9% (0.0~30.0mg/L)
D.O. Accuracy/res.	+/-3% of F.S. +1 digit ; res.: 0.1
Temp. range	-5~60.0°C
Temp. Accuracy/res.	+/-0.5°C ; 0.1
Compatible probe	pH probe, EC probe and D.O probe Could be all used on one meter at the same time
LCD size(mm)	32.5(H)x54(W)
Operating temp. & RH%	0~50°C, Humidity<80%
Storage temp. & RH%	0~60°C, Humidity < 90%
Dimension(mm)	169(L)x78.3(W)x43.4(H)
Weight	200g
Power	4PCS AAA Batteries
Standard Package	Meter/Manual/Carry case/Battery
Standard Probe	PH probe/Cond. Probe/D.O.Probe/D.O. Electrolyte/ 2 Membrane set/Cable clip (User can decide which probe to be included as standard)

Ordering Code

VZ86031AZ0, 86031 meter only
VZ86031AZ1, 86031 meter +DO probe
VZ86031AZ2, 86031 meter +pH+EC probe
VZ86031AZ3, 86031 meter +pH+EC+DO probe
VZ863PAZ, low ion pH probe for 86031/86021/84051
VZ833PAZ, EC probe for 86031/86021/84051
VZ843PAZ, DO probe for 86031/86021/84051
VZ84PAAZ, DO membrane+electrolyte for 843P,8413P

*Available for EB project



Authorized Distributor
APL ASIA CO., LTD.
11/129-132 Moo.5 Lamlukka Rd.,T.Kookut, A.Lamlukka, Pathumthani 12130 Thailand.
TEL. 0-2995-4461-4
www.apl-asia.com
EMAIL : sales@apl-asia.com
LINE@ : @APL-ASIA

2024.08 V2.2