
FLOWITA EVO


Wall-mounted monobloc pump, dismountable, for the condensate removal from air conditioners up to 10kW / 36000BTU.

Ref: DE05LCC440

NEW








Hose diameter
Discharge : 6/9 mm - not supplied

SPECIFICATIONS


Flowrate max	**13.2 l/h**
Discharge head	**10 m**
Electrical power	**19W**
Voltage	**220-240V 50/60Hz**
Alarm*	**Optional**
Noise level**	
Protection rating	**IP24**
Thermal protection	**Yes**
Operating cycle***	**100%**
Power cable	**0.8 m**
Tank capacity	**170 ml**
Dimensions	**135 x 57 x 106.5 mm**

* Alarm option available on request.
** Notation from 1 wave (≤ 20 dBA) to 6 waves (> 45 dBA)
*** The pump is able to run 100% of the time if necessary.

FLOWRATE



BENEFITS



Dismountable

The FLOWITA EVO can be disassembled in seconds!

Front panel, tank, suction tube... all the elements are removable.

Installation and maintenance has never been so quick and easy!



100ml pumping cycles

Its large reservoir allows the pump to operate optimally: larger and less frequent pumping cycles.

Extremely silent

The most discreet wall-mounted pump on the market!

Quick installation

The FLOWITA EVO can be installed easily and quickly underneath any air conditioner.

IP24 protection

Protected against water splashes.

CONTENTS

Pump - Screws and rawlplugs



Authorized Distributor
APL ASIA CO., LTD.
11/129-132 Moo.5 Lamlukka Rd.,T.Kookut, A.Lamlukka, Pathumthani 12130 Thailand.
TEL. 0-2995-4461-4
www.apl-asia.com
EMAIL : sales@apl-asia.com
LINE@ : @APL-ASIA