EN

Mini Orange®

CONDENSATE REMOVAL PUMP



The world's best selling mini pump offers unrivalled reliability and performance.

- 12L/h max. flow
- 10m max. rec. head (flow rate 6L/h)
- 21dB(A) @ 1m

KEY FEATURES

- Submersible secondary reservoir included
- Plug & play
- Anti siphon device


SUITABILITY





- Up to 16kW / 54,000Btu/h
- High wall split systems; Ducted units; Floor standing & Chassis units

✓**Perfect for...** Smaller commercial & domestic units

0.25 kg†







MINI ORANGE @ 230 VAC 50Hz	
Max. flow	12L/h @ 0m head
Max. rec. head	10m
Max. suction lift	2m
dB(A) @ 1m	21
Power supply	230 VAC, 0.11A, 16W, 50/60Hz
Rated	Non continuous
Class	II appliance ⧈
Max. unit output	16kW / 54,000Btu/h
Max. water temp	40°C / 104°F
Discharge tube	6mm ID
IP Protection	IP21
Safety switch	3.0A Normally closed
Thermal protection	✓
Fully potted	✓
Self priming	✓

Information correct at time of going to press.

MINI ORANGE OPTIONS	
Mini Orange (Europe)	FP2212

† Pump only

IN THE BOX

Mini Orange pump • 1.5m Plug & play power cable • Reservoir • Reservoir lid with 1.5m sensor cable • Submersible reservoir • Anti siphon device • Float & filter • 1.5m Suction tube 6mm ID • 220mm Orange inlet hose 14mm ID • 150mm Vinyl breather tube 6mm ID • Drain connector kit • Fixing kit • Install manual

Download manual at aspenpumps.com

View install video at aspenpumps.com

SUGGESTED XTRA ACCESSORIES

Description		Part No.
1 Amp Fuse		FP2620
Tube To Soil Stack Adaptor		FP2038
Vinyl Tube Braided 1/4" (6mm)		AX5100
4.3m Mini/Maxi orange extension kit		FP2940

For more installation accessories take a look at our Aspen Xtra range