NecooL

**IRD-300 Infrared Leak Detector**

**(4 Level sensitivity+Alarm probe led + 3 UV light+ 2 led light)**

10 years sensor lifetime

2g or 3g/year sensitivity per EN14624

Quick charging lithium ion battery

2.8-inch color LCD display

Superior sensitivity and strong anti-interference performance

Detect all HCFCs, HFCs, HFOs, (including A2Ls)

State-of-the-art infrared sensor

Sensitivity multilevel adjustment,2g/a(stationary);3g/a (in motion)

Flashing light tip, loud beeper and LCD bar graph

Two high- intensity LED inspection light, unafraid of dark environments (only IRD-300)

Three LED UV lights with 395-415 nm wave length is optimum for a/c dye fluorescence only IRD-300)

Two rechargeable 18650 lithium batteries can be disassembled and replaced

Audio mute mode

| Item No. | IRD-300 |
|---|---|
| Refrigerants | CFCs/HCFCs/HFCs/HFOs |
| Sensor life | 10 years |
| Sensitivity | 2g/yr |
| Alarm mode | Audible and visual alarm and flashing probe LED |
| Response time | Instantaneous |
| Warm-up me | 30s |
| Auto off me | 10 minutes of inactivity |
| Battery | 2*18650 Lithium battery |
| Operating temperature | -10°C~50°C |
| Overall size | 210*60*36 inch. |
| Probing length | 420 mm. |
| Four sensitivity levels | Low, Medium, High, Super high |




**รับประกันตัวเครื่อง 1 ปี**

APL ASIA

บริษัท เอพีแอล เอเซีย จำกัด
WWW.APL-ASIA.COM
Tel 02-9954461-4 Email: sales@apl-asia.com Line: @APL-ASIA
11/129-132 หมู่ 5 ถนน ลำลูกกา 5 ตำบลคูคต อำเภอลำลูกกา ปทุมธานี 12130

SCAN HERE

LINE