

7,5 kW | 24 000 Btu

EE600

Mini-Condensate Pump



6 l/h
1,6 gal/h



6 m
19,7 ft



28 db(A) DIN EN 3745
~ < 22 db(A) DIN EN 3744

Description

The EE600 system consists of a pump unit and a separate 3-level float switch sensor. It comes with mounting accessories like pads of double-sided padded tape to fix the float switch and an anti-shock mount for the pump unit.

Usage

This float type pump is mainly used in air conditioners with a limited space inside, e. g. wall mounted mini split and ceiling units. The small sensor can easily be adapted to the air conditioner's condensate drain hose.

Special features

- integrated buzzer (beeper), can be deactivated
- Impervious to blockage or contamination due to unique valve design and large piston bore

Performance





Inside the box

- integrated buzzer (beeper)
- pump block with vibration dampers
- three-stage float switch with dirt retainer
- 300mm acoustic damping/reducing discharge tube (6mm ID) with hose connector
- PVC vent hose
- 2x cable ties
- 2x double sided padded tape
- silicon hose (internal diameter 15 mm, length 40mm - connects to split drain hose)



Technical data

For air conditioners up to [kW]	7,5
Drive	Solenoid pump
Mains voltage & frequency	230V, 50/60Hz
Power consumption [W]	Operation: 13 Standby: 1
Max. flow rate [l/h]	6
Max. delivery height [m]	6
Max. suction height [m]	1,5
Pump unit L x W x H [mm]	77 x 32 x 50
Float switch L x W x H [mm]	82 x 39 x 39
Switch points float switch [mm]	Alarm: max. 23 Start: 18 ±1 Stop: 14 ±1
Pressure, suction hose [mm]	6 x 1,5
Alarm switch	integrated buzzer (beeper)



Installation video:



SCAN ME