

RVG-10A

Compatible with high and low pressure measurements

High pressure mode: Measure condensation temperature and Sub-cooling

Low pressure mode: Measure evaporation temperature and Super-heating

Waterproof

The instrument is protected to IP65 against low-pressure water jets

Note: Cannot be immersed directly in water

Ball valve

The ball valve has a short opening and closing time and allows for precise control of the charge volume

Rich measurement functions

Four Measurement Functions: Pressure Measurement, Temperature Measurement, Leak Test, AC ECG

Exhaust valve

Pressure venting simplifies venting for greater convenience and safety

Specifications

Item No.	RVG-10A
Pressure Range	-14.5~800 psi
Accuracy	±0.5%FS
Resolution	0.5 psi
Temperature range	-50°C ~ 150°C / -58°F ~ 302°F
Temperature Accuracy	±0.5°C / ±0.9°F
Temperature Resolution	0.1°C / 0.2°F
Pressure units	kPa, MPa, bar, psi, kg/cm ²
Temperature units	°C, °F
Operating temperature and humidity	-10~50°C, 35%~85% RH
Battery	2# AAA
Refrigerant	88 types



รับประกันตัวเครื่อง 1 ปี



บริษัท เอพีแอล เอเชีย จำกัด

WWW.APL-ASIA.COM

Tel 02-9954461-3 Email: sales@apl-asia.com Line: @APL-ASIA
11/129-132 หมู่ 5 ถนน ลำลูกกา 5 ตำบลคูคต อำเภอลำลูกกา ปทุมธานี 12130

SCAN HERE

