



FEATURES

- IP67 water proof housing to work for almost all kinds of environments.
- PT temperature sensor for less environmental dependent reading.
- High precision.
- Large display easy-to-read.
- LCD Back Light

SPECIFICATIONS

Sensor type: PT-1000

Measuring principle: 2-wire technology

Measurement range: -100 ~ 300 °C

Accuracy: ± 0.3 °C

Resolution: 0.1 °C

Sample rate: 1 time per second

Protection class: IP 67

Battery type: Lithium coil cell 3V type CR 2477

Battery life: Approx. 2 years

Auto power off: 10 min.

Operation temperature / humidity:

0 °C ~ 50 °C (32 °F ~ 122 °F), 0 ~ 80% RH

Storage temperature / humidity:

-10°C ~ 60°C (14°F ~ 140 °F), 0 ~ 80% RH

Dimensions: 120 mm(L) x 60 mm(W) x 24.5 mm(H)

Weight: Approx. 230g

Accessories:

Pt-1000 probe (class A), battery, instruction manual



V.115.04.15

* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER®



Authorized Distributor

APL ASIA CO., LTD.

11/129-132 Moo.5 Lamlukka Rd., T.Kookut, A.Lamlukka, Pathumthani 12130 Thailand.

TEL: 0-2995-4461-3, FAX: 0-2995-4464

www.apl-asia.com

EMAIL: sales@apl-asia.com

LINE@: @APL-ASIA



Sedex®