CENTER 389

CARBON DIOXIDE LEAK DETECTOR

FEATURES





DC 5V Jack

CO2 Refrigerant Leakage Detector is the perfect tool for maintaining industrial heat extraction, heat pump water heaters, chilled warehousing, supermarkets, shopping vessels, commercial refrigeration and automotive air conditioning. This unit uses a newly developed optical gas sensor which is extremely sensitive to variety of R744 Refrigerant.



SPECIFICATIONS

- Microprocessor Control with advanced digital signal processing.
- Multi color visual display.
- High-median-Low leak sensitivity selector.
- Low battery indication.
- Optical gas sensor.
- Detection gas: R744 (CO2).
- Carrying case included.
- 15.5” (40 CM) flexible stainless probe.
- Ambient concentration reset.
- Peak function – find leaks in noisy environments.
- Mute function.
- Auto-matic zero and background compensation.
- Warm-up Time: 45 Seconds.
- Operating Temperature: 0 to 40°C(32 to 104°F)
- Dimension: 222 x 66 x 51 mm
- Weight: 418g(with batteries)
- Power Usage: 3.7vdc rechargeable lithium Batteries.
- Battery Life: Approx. 7hrs under normal use
- AC Adapter: @5V 1A

CE

Certificate No. 49Q13377

* The specifications and other information in this catalogue are subject to change without prior notice.

CENTER®
CENTER TECHNOLOGY CORP.
4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,
New Taipei City 238, Taiwan
TEL: 886-2-26763926 E-Mail : center@centertek.com
FAX: 886-2-26763925 http : //www.centertek.com

Authorized Distributor
APL ASIA CO., LTD.
11/129-132 Moo.5 Lamlukka Rd.,T.Kookut, A.Lamlukka, Pathumthani 12130 Thailand.
TEL. 0-2995-4461-4
www.apl-asia.com
EMAIL : sales@apl-asia.com
LINE@ : @APL-ASIA

VER.00 2017.03.07