EN

Low Profile ERRP

CONDENSATE REMOVAL PUMP



Designed exclusively to fit underneath retail refrigeration cabinets the lightweight plastic ERRP (Economical Retail Refrigeration Pump) allows for the removal of defrost and contaminated water.

190L/h max. flow

21m max. rec. head (flow rate 10L/h)

KEY FEATURES


- Lightweight & slim
- Easy to clean and carry
- Filter to catch debris
- Plug & play

SUITABILITY

- Refrigeration units; cold store cabinets


✓ **Perfect for...** Single & multiple refrigeration units





LOW PROFILE ERRP @ 230 VAC 50Hz	
Max. flow	190L/h @ 0m head
Max. rec. head	21m
Tank capacity	3.5L
dB(A) @ 1m	60
Power supply	230 VAC, 0.2A, 50/60Hz
Rated	Non continuous
Class	I appliance
Max. unit output	n/a
Max. water temp	40°C / 104°F
Inlet/outlet	50mm in, 10mm out
IP Protection	IP24
Safety switch	3.0A Normally closed
Thermal protection	✓
Fully potted	n/a
Self priming	n/a

Information correct at time of going to press.



SUGGESTED XTRA ACCESSORIES

Description	Part No.
1 Amp Fuse	FP2620
Tube To Soil Stack Adaptor	FP2038
Vinyl Tube Braided 3/8" (10mm)	AX5101

For more installation accessories take a look at our Aspen Xtra range

LOW PROFILE ERRP OPTIONS

Low Profile ERRP – top inlet	FP2597
Low Profile ERRP – side inlet	FP2805

* Side inlet only

IN THE BOX

Low Profile ERRP pump • 2m Plug & play power cable • 1½" BSP connector (for 40mm ID waste pipe)* • Install manual

Download manual at aspenpumps.com