EN

ERRP

CONDENSATE REMOVAL PUMP



Made of robust plastic, the lightweight ERRP (Economical Retail Refrigeration Pump) effectively pumps away defrost water and filters debris.

225L/h max. flow

35m max. rec. head (flow rate 25L/h)

KEY FEATURES


- Top & side inlet options
- Easy to clean & carry
- Filter to catch debris
- Plug & play

SUITABILITY

- Refrigeration units; cold store cabinets


✓**Perfect for...** Multiple refrigeration units





ERRP @ 230 VAC 50Hz	
Max. flow	225L/h @ 0m head
Max. rec. head	35m
Tank capacity	11L
dB(A) @ 1m	60
Power supply	230 VAC, 0.2A, 50/60Hz
Rated	Non continuous
Class	I appliance
Max. unit output	n/a
Max. water temp	40°C / 104°F
Inlet/outlet	50mm in, 10mm out
IP Protection	IP24
Safety switch	3.0A Normally closed
Thermal protection	✓
Fully potted	n/a
Self priming	n/a

Information correct at time of going to press.



SUGGESTED XTRA ACCESSORIES

Description		Part No.
1 Amp Fuse		FP2620
Tube To Soil Stack Adaptor		FP2038
Vinyl Tube Braided 3/8" (10mm)		AX5101

For more installation accessories take a look at our Aspen Xtra range

ERRP OPTIONS

ERRP – top inlet	FP2318
ERRP – side inlet	FP2320

* Side inlet only

IN THE BOX

ERRP pump • 2m Plug & play power cable • 1½" BSP connector (for 40mm ID waste pipe)* • Install manual

Download manual at aspenpumps.com