# IRD-200 Refrigerant leak detector

10 years sensor lifetime
2g or 3g/year sensitivity per EN14624
Quick charging lithium lon battery
Superior sensitivity and strong anti-interference performance
Flashing probe LED ,more accurate positioning ofleakage points
Detect all HCFCs,HFCs,HFOs, (including A2Ls)

## Specifications

| | |
|---|---|
| Item No. | IRD-200 |
| Refrigerants | CFCs / HCFCs / HFCs / HFOs |
| Sensor life | 10 years |
| Sensitivity | 2 g/yr |
| Alarm mode | Audible and visual alarm |
| Response time | Instantaneous |
| Warm-up time | 30 s |
| Auto-off time | 10 minutes of inactivity |
| Battery | 2 × 18650 lithium batteries |
| Operating temperature | -10°C to 50°C |
| Overall size | 210 × 60 × 36 inch |
| Probing length | 420 mm |
| Sensitivity levels | Low, Medium, High, Super high |




**รับประกันตัวเครื่อง 1 ปี**

APL-ASIA

บริษัท เอพีแอล เอเซีย จำกัด
WWW.APL-ASIA.COM
Tel 02-9954461-4 Email: sales@apl-asia.com Line: @APL-ASIA
11/129-132 หมู่ 5 ถนน ลำลูกกา 5 ตำบลคูคต อำเภอลำลูกกา ปทุมธานี 12130

SCAN HERE
LINE